# GoProtect

# **HEAVY DUTY SURFACE CLEANER**



**Before Cleaning After Cleaning Before Cleaning** 

# **Natural Stone**

# A CLEANER TO REMOVE GENERAL SOILING FROM SURFACES

#### **PRODUCT DESCRIPTION**

- A powerful and effective degreasing cleaner.
- Formulated with biodegradable components.
- Removes stubborn, greasy stains & soiling caused by either atmospheric or industrial pollution.
- Particularly suitable for various indoor and outdoor horizontal substrates: floors, paved ground surfaces... made of : concrete, cement, natural and artificial stone, terracotta, porcelain, tiling, stoneware, marble, etc.
- Does not alter the appearance or aesthetics of surfaces being treated.

### ADVANTAGES AND CHARACTERISTICS

- Non-corrosive to most surfaces when used diluted.
- Do not use neat on aluminium.
- Water-borne product.
- No need to pH neutralize after rinsing when used in its diluted state
- Particularly suitable for horizontal surfaces.

# **TECHNICAL DATA**

Physical State at 20 °C : Liquid

Appearance : Pale Yellow

: 13 ± 0.5

Boiling point [°C] : 100 °C

Density : 1.06

Does not alter surface being treated

Biodegradable.

Easy to use;

Solubility in water [vol/vol]: Fully soluble Flash Point [°C] : Not applicable

Always carry out a test on a small area first

VOC : 80 g/l

Odour : Mild characteristic odour

#### **APPLICATION**

- Shake the container well before use
- Always test apply on a small hidden portion of the substrate requiring treatment.
- Use neat on heavy contaminated surfaces or diluted by adding 1 part product with up to 20 parts water depending on the staining to be removed:
  - o Heavily soiled surfaces eg. Garage workshops use neat
  - Worktops & kitchen floors 1 part product + 5-10parts water
- Use a low pressure hand spray unit or brush.
- Apply the product liberally.
- Allow the product to act on surfaces for:
  - o lightly soiled: 1-2 minutes
  - o heavily soiled: 5-10 minutes
  - o for deeply penetrating lubricating oil stains it may be necessary to apply the product twice allowing 10 minutes between applications.
- Whilst the surface is still wet, thoroughly rinse external surfaces with a high pressure water jet at 80-100 bar. For optimum results use hot water at around 80°C, and vacuum up using a wet & dry vacuum.
- Treated substrates do not need to be neutralised. (test)
- To prevent future soiling, it is recommended to use a suitable protection treatment such as: **GoProtect MULTI SURFACE PROTECTOR.**

#### **PACKAGING**

1 litre; 5 litre container

# **APPLICATION RATE**

• The figures below are approximate and should be used only as a general guideline:

5 -15 m<sup>2</sup> / litre

# **CLEANING EQUIPMENT**

• Clean tools and equipment immediately after use with water

#### **STORAGE**

- Keep in a cool, dry place
- Keep away from extreme cold, do not store in conditions below 5°C
- Shelf Life: 24 months in unopened containers, stored in recommended conditions.

# **RECOMMENDATIONS**

- Wear protective gloves and glasses, and appropriate clothing whilst using the product.
- Do not dilute or mix with any other product.
- Do not apply during rain or frost and when surface and air temperature is < 5°C.</li>

#### **HEALTH AND SAFETY**

• Refer to current msds.

# KEEP OUT OF THE REACH OF CHILDREN

#### **TECHNICAL ASSISTANCE**

#### P&I Rowe Ltd, Treetops, Foscote Rise, Banbury. OX16 9XS.

**Important:** The contents of this document are the result of experience gained with this product. The company cannot be held liable for its use in individual cases. For more information, please see the Material Safety Data Sheet.

Product Code: Rog Date of last update: 23/06/16